

## FL 635 - Tekniska specifikationer



### Description

FL 635 är ett flotationsradialdäck som lämpar sig för körning på både väg och åker. Det speciella blockmönstret är särskilt konstruerat för balpressarbeten. FL 635 säkerställer jämn tryckfördelning mot marken över hela avtrycket och minskar drastiskt jordpackningen för att bevara den värdefulla grödan. Däcket besitter fantastiska självrensande egenskaper och erbjuder såväl hållbarhet som dragförmåga och utmärkt hastighet.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Lantbruk: Balpress

|           |               |
|-----------|---------------|
| Version   | STANDARD      |
| Type      | TL            |
| Tyre Size | 710/40 R 22.5 |
| LI/SS     | 161 D         |

## Dimensions US Standard

|                              |                 |
|------------------------------|-----------------|
| Usa code                     | 94053285        |
| Section Width (inch)         | 28.6            |
| Overall Diameter (inch)      | 44.9            |
| Static Loaded Radius (inch)  | 20.1            |
| Rolling Circumference (inch) | 136.5           |
| Rim Rec                      | AG 24.00        |
| ECE                          | E11-106R-003014 |

## Load capacity (lbs)

| mph / psi | 12   | 15   | 17   | 23   | 29    | 35    | 41    | 46    | 52    | 58    |
|-----------|------|------|------|------|-------|-------|-------|-------|-------|-------|
| 45        | 2980 | 3390 | 3810 | 4740 | 5390  | 6230  | 7050  | 7700  | 8450  | 9280  |
| 40        | 3260 | 3730 | 4190 | 5200 | 5920  | 6830  | 7750  | 8470  | 9280  | 10200 |
| 30        | 3960 | 4520 | 5070 | 6300 | 7160  | 8280  | 9390  | 10250 | 11240 | 12350 |
| 25        | 4440 | 5070 | 5690 | 7080 | 8050  | 9290  | 10550 | 11520 | 12620 | 13870 |
| 20        | 4940 | 5630 | 6320 | 7860 | 8940  | 10320 | 11710 | 12790 | 14020 | 15400 |
| 15        | 5160 | 5890 | 6610 | 8220 | 9350  | 10800 | 12260 | 13380 | 14670 | 16110 |
| 5         | 5870 | 6700 | 7530 | 9370 | 10650 | 12300 | 13950 | 15230 | 16710 | 18350 |

Printed on 4/24/2024 5:18 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..