

FLOTATION 647 - Tekniska specifikationer



Description

FLOTATION 647 är ett redskapsdäck med utmärkt dragförmåga på mjuk mark och gräsmark. Förutom utmärkta självrensande egenskaper har det specialdesignade mönstret en bred kontaktyta, vilket säkerställer optimalt tryck mot marken och överlägsen prestanda på mjuk mark.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Arbetsfordon

Version	STANDARD
Type	TL
Tyre Size	260/75 - 15.3
LI/SS DRIVE WHEEL	119 A8
LI/SS FREE ROLLING	131 A8

Dimensions International Standard

Section Width (mm)	275
Overall Diameter (mm)	785
Static Loaded Radius (mm)	363
Rolling Circumference (mm)	2380
Rim Rec	9.00
ECE	E11-106R-005838

Load capacity (Kg)

km/h / bar	5.50
40 FR	1950
40 DW	1360

Printed on 4/20/2024 3:48 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..