

## FLOTATION 648 - Tekniska specifikationer



### Description

FLOTATION 648 lämpar sig särskilt väl för åker- och vägtransporter samt spridningsarbeten. Vissa storlekar är designade för skördemaskiner/balpressar. Den speciella mönsterdesignen möjliggör körning av tunga laster vid lågt lufttryck, och garanterar samtidigt låg jordpackning och bevarade grödor.

### UM

US Standard

### Construction

 BIAS

### Machinery

Lantbruk: Balpress • Höskördemaskin • Spridare

Version	STANDARD
Type	TL
Tyre Size	350/65 - 22.5
LI/SS DRIVE WHEEL	139 A8/135 B
LI/SS FREE ROLLING	151 A8/147 B

## Dimensions US Standard

Usa code	94030644
Ply Rating	18
Section Width (inch)	14.1
Overall Diameter (inch)	40.6
Static Loaded Radius (inch)	17.8
Rolling Circumference (inch)	120.8
Rim Rec	AG 11.75
ECE	E11-106R-004551

## Load capacity (lbs)

mph / psi	29	44	58	73
5 FR	6240	7900	9350	10650
10 FR	5610	7110	8420	9580
20 FR	4980	6320	7480	8520
25 FR	4450	5640	6680	7610
30 FR	4010	5080	6010	6780
5 DW	4390	5560	6590	7500
10 DW	3950	5000	5930	6750
20 DW	3510	4440	5270	6000
25 DW	3130	3970	4710	5360
30 DW	2820	3570	4230	4810

Printed on 12/8/2023 12:44 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..