

FLOTATION 648 - Tekniska specifikationer



Description

FLOTATION 648 lämpar sig särskilt väl för åker- och vägtransporter samt spridningsarbeten. Vissa storlekar är designade för skördemaskiner/balpressar. Den speciella mönsterdesignen möjliggör körning av tunga laster vid lågt lufttryck, och garanterar samtidigt låg jordpackning och bevarade grödor.

UM

US Standard

Construction

 BIAS

Machinery

Lantbruk: Balpress • Höskördemaskin • Spridare

Version	STANDARD
Type	TL
Tyre Size	500/50 - 17
LI/SS DRIVE WHEEL	128 A8/124 B
LI/SS FREE ROLLING	140 A8/136 B

Dimensions US Standard

Usa code	94039814
Ply Rating	10
Section Width (inch)	20.1
Overall Diameter (inch)	37.2
Static Loaded Radius (inch)	16.4
Rolling Circumference (inch)	108.3
Rim Rec	AG 16.00
ECE	E4-106R-002713

Load capacity (lbs)

mph / psi	22	25	29
5 FR	6530	7020	7720
10 FR	5870	6320	6940
20 FR	5220	5620	6170
25 FR	4660	5020	5510
30 FR	4200	4520	4940
5 DW	4700	5050	5560
10 DW	4220	4540	5000
20 DW	3750	4030	4440
25 DW	3350	3600	3970
30 DW	3020	3240	3530

Printed on 11/29/2023 4:23 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..