

FLOTATION 648 - Tekniska specifikationer



Description

FLOTATION 648 lämpar sig särskilt väl för åker- och vägtransporter samt spridningsarbeten. Vissa storlekar är designade för skördemaskiner/balpressar. Den speciella mönsterdesignen möjliggör körning av tunga laster vid lågt lufttryck, och garanterar samtidigt låg jordpackning och bevarade grödor.

UM

US Standard

Construction

 BIAS

Machinery

Lantbruk: Balpress • Höskördemaskin • Spridare

Version	STANDARD
Type	TL
Tyre Size	500/50 - 22.5
LI/SS DRIVE WHEEL	140 A8/136 B
LI/SS FREE ROLLING	152 A8/148 B

Dimensions US Standard

Usa code	94027798
Ply Rating	12
Section Width (inch)	19.7
Overall Diameter (inch)	42.1
Static Loaded Radius (inch)	18.7
Rolling Circumference (inch)	126
Rim Rec	AG 16.00

Load capacity (lbs)

mph / psi	22	29	32
5 FR	8750	10350	10960
10 FR	7870	9310	9870
20 FR	7000	8290	8760
25 FR	6250	7400	7830
30 FR	5620	6660	6940
5 DW	6170	7300	7720
10 DW	5560	6570	6940
20 DW	4940	5840	6170
25 DW	4410	5210	5510
30 DW	3970	4700	4940

Printed on 12/8/2023 1:18 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..