

## FLOTATION 648 - Tekniska specifikationer



### Description

FLOTATION 648 lämpar sig särskilt väl för åker- och vägtransporter samt spridningsarbeten. Vissa storlekar är designade för skördemaskiner/balpressar. Den speciella mönsterdesignen möjliggör körning av tunga laster vid lågt lufttryck, och garanterar samtidigt låg jordpackning och bevarade grödor.

### UM

International Standard

### Construction

 BIAS

### Machinery

Lantbruk: Balpress • Höskördemaskin • Spridare

Version	STANDARD
Type	TL
Tyre Size	500/50 - 22.5
LI/SS DRIVE WHEEL	146 A8/142 B
LI/SS FREE ROLLING	158 A8/155 B

## Dimensions International Standard

Ply Rating	16
Section Width (mm)	500
Overall Diameter (mm)	1070
Static Loaded Radius (mm)	475
Rolling Circumference (mm)	3200
Rim Rec	AG 16.00
ECE	E4-106R-001560

## Load capacity (Kg)

km/h / bar	2.60	2.80	3.00
10 FR	5475	5710	5950
20 FR	4925	5140	5355
30 FR	4380	4570	4760
40 FR	3910	4080	4250
50 FR	3520	3670	3875
10 DW	3865	4030	4200
20 DW	3480	3630	3780
30 DW	3090	3225	3360
40 DW	3760	2880	3000
50 DW	2485	2590	2650

Printed on 12/8/2023 1:19 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..