

## FLOTATION 648 - Tekniska specifikationer



### Description

FLOTATION 648 lämpar sig särskilt väl för åker- och vägtransporter samt spridningsarbeten. Vissa storlekar är designade för skördemaskiner/balpressar. Den speciella mönsterdesignen möjliggör körning av tunga laster vid lågt lufttryck, och garanterar samtidigt låg jordpackning och bevarade grödor.

### UM

US Standard

### Construction

 BIAS

### Machinery

Lantbruk: Balpress • Höskördemaskin • Spridare

Version	STANDARD
Type	TL
Tyre Size	600/50 - 22.5
LI/SS DRIVE WHEEL	155 A8/151 B
LI/SS FREE ROLLING	167 A8/163 B

## Dimensions US Standard

Usa code	94030781
Ply Rating	18
Section Width (inch)	24.1
Overall Diameter (inch)	46.1
Static Loaded Radius (inch)	20.1
Rolling Circumference (inch)	137.8
Rim Rec	AG 20.00
ECE	E4-106R-002275

## Load capacity (lbs)

mph / psi	39	41	42
5 FR	16130	16480	16820
10 FR	14520	14840	15130
20 FR	12900	13180	13460
25 FR	11520	11770	12010
30 FR	10370	10590	10750
5 DW	11460	11720	11960
10 DW	10320	10540	10770
20 DW	9170	9370	9570
25 DW	8190	8370	8540
30 DW	7370	7530	7610

Printed on 12/8/2023 1:23 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..