# FLOTATION 648 - Tekniska specifikationer

## Description

FLOTATION 648 lämpar sig särskilt väl för åker- och vägtransporter samt spridningsarbeten. Vissa storlekar är designade för skördemaskiner/balpressar. Den speciella mönsterdesignen möjliggör körning av tunga laster vid lågt lufttryck, och garanterar samtidigt låg jordpackning och bevarade grödor.

## UM

International Standard

## Construction

BIAS

## Machinery

Lantbruk: Balpress • Höskördemaskin • Spridare

| | |
|---|---|
| **Version** | DUAL BEAD |
| **Type** | TL |
| **Tyre Size** | 600/55 - 22.5 |
| **LI/SS DRIVE WHEEL** | 160 A8/156 B |
| **LI/SS FREE ROLLING** | 173 A8/169 B |

## Dimensions International Standard

| | |
|---|---|
| **Ply Rating** | 20 |
| **Overall Width (mm)** | 600 |
| **Overall Diameter (mm)** | 1230 |
| **Static Loaded Radius (mm)** | 540 |
| **Rolling Circumference (mm)** | 3716 |
| **Rim Rec** | AG 20.00 |
| **ECE** | E11-106R-004393 |

## Load capacity (Kg)

| km/h / bar | 3.00 | 3.10 | 3.20 |
|---|---|---|---|
| **10 FR** | 8765 | 8930 | 9100 |
| **20 FR** | 7890 | 8040 | 8190 |
| **30 FR** | 7010 | 7145 | 7280 |
| **40 FR** | 6260 | 6380 | 6500 |
| **50 FR** | 5635 | 5740 | 5800 |
| **10 DW** | 6070 | 6180 | 6300 |
| **20 DW** | 5460 | 5565 | 5670 |
| **30 DW** | 4855 | 4945 | 5040 |
| **40 DW** | 4335 | 4415 | 4500 |
| **50 DW** | 3900 | 3975 | 4000 |

Printed on 4/25/2024 11:15 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..