

## FLOTATION 648 - Tekniska specifikationer



### Description

FLOTATION 648 lämpar sig särskilt väl för åker- och vägtransporter samt spridningsarbeten. Vissa storlekar är designade för skördemaskiner/balpressar. Den speciella mönsterdesignen möjliggör körning av tunga laster vid lågt lufttryck, och garanterar samtidigt låg jordpackning och bevarade grödor.

### UM

US Standard

### Construction

BIAS

### Machinery

Lantbruk: Balpress, Höskördemaskin, Spridare

Version	DUAL BEAD
Type	TL
Tyre Size	600/55 - 22.5
LI/SS DRIVE WHEEL	160 A8/156 B
LI/SS FREE ROLLING	173 A8/169 B

### Dimensions US Standard

Usa code	94045280
Ply Rating	20
Overall Width (inch)	23.6
Overall Diameter (inch)	48.4
Static Loaded Radius (inch)	21.3
Rolling Circumference (inch)	146.3
Rim Rec	AG 20.00
ECE	E11-106R-004393

## Load capacity (lbs)

mph / psi	44	45	46
5 FR	19320	19690	20060
10 FR	17390	17720	18050
20 FR	15450	15750	16050
25 FR	13800	14060	14330
30 FR	12420	12650	12790
5 DW	13380	13620	13890
10 DW	12040	12270	12500
20 DW	10700	10900	11110
25 DW	9560	9730	9920
30 DW	8600	8760	8820

Printed on 04/12/2022 02:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..