

FLOTATION 648 - Tekniska specifikationer



Description

FLOTATION 648 lämpar sig särskilt väl för åker- och vägtransporter samt spridningsarbeten. Vissa storlekar är designade för skördemaskiner/balpressar. Den speciella mönsterdesignen möjliggör körning av tunga laster vid lågt lufttryck, och garanterar samtidigt låg jordpackning och bevarade grödor.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Balpress • Höskördemaskin • Spridare

Version	STANDARD
Type	TL
Tyre Size	600/55 - 26.5
LI/SS DRIVE WHEEL	159 A8/156 B
LI/SS FREE ROLLING	170 A8/167 B

Dimensions International Standard

Ply Rating	16
Section Width (mm)	611
Overall Diameter (mm)	1354
Static Loaded Radius (mm)	581
Rolling Circumference (mm)	4017
Rim Rec	AG 20.00
ECE	E4-106R-002276

Load capacity (Kg)

km/h / bar	2.20	2.40	2.60
10 FR	7615	8015	8400
20 FR	6855	7215	7560
30 FR	6095	6410	6720
40 FR	5440	5725	6000
50 FR	4895	5155	5450
10 DW	5560	5845	6125
20 DW	5000	5260	5515
30 DW	4445	4675	4900
40 DW	3970	4175	4375
50 DW	3575	3760	4000

Printed on 11/29/2023 4:18 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..