

## FLOTATION 648 - Tekniska specifikationer



### Description

FLOTATION 648 lämpar sig särskilt väl för åker- och vägtransporter samt spridningsarbeten. Vissa storlekar är designade för skördemaskiner/balpressar. Den speciella mönsterdesignen möjliggör körning av tunga laster vid lågt lufttryck, och garanterar samtidigt låg jordpackning och bevarade grödor.

### UM

US Standard

### Construction

 BIAS

### Machinery

Lantbruk: Balpress • Höskördemaskin • Spridare

Version	HD
Type	TL
Tyre Size	650/65 - 30.5
LI/SS DRIVE WHEEL	169 A8/165 B
LI/SS FREE ROLLING	181 A8/178 B

## Dimensions US Standard

Usa code	94030279
Ply Rating	18
Section Width (inch)	26.4
Overall Diameter (inch)	65.4
Static Loaded Radius (inch)	28
Rolling Circumference (inch)	194.3
Rim Rec	AG 20.00
ECE	E11-106R-004563

## Load capacity (lbs)

mph / psi	33	35	36
5 FR	24240	24860	25460
10 FR	21810	22380	22920
20 FR	19400	19880	20370
25 FR	17320	17760	18190
30 FR	15590	15980	16530
5 DW	17050	17480	17900
10 DW	15340	15740	16110
20 DW	13650	13990	14320
25 DW	12180	12490	12790
30 DW	10970	11240	11350

Printed on 11/29/2023 4:55 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..