

## FLOTATION 648 - Tekniska specifikationer



### Description

FLOTATION 648 lämpar sig särskilt väl för åker- och vägtransporter samt spridningsarbeten. Vissa storlekar är designade för skördemaskiner/balpressar. Den speciella mönsterdesignen möjliggör körning av tunga laster vid lågt lufttryck, och garanterar samtidigt låg jordpackning och bevarade grödor.

### UM

International Standard

### Construction

BIAS

### Machinery

Lantbruk: Balpress, Höskördemaskin, Spridare

Version	HD
Type	TL
Tyre Size	700/40 - 22.5
LI/SS DRIVE WHEEL	160 A8/156 B
LI/SS FREE ROLLING	173 A8/169 B

### Dimensions International Standard

Ply Rating	18
Section Width (mm)	700
Overall Diameter (mm)	1170
Static Loaded Radius (mm)	510
Rolling Circumference (mm)	3537
Rim Rec	AG 24.00
ECE	E4-106R-002281

## Load capacity (Kg)

km/h / bar	2.80	3.00	3.20
10 FR	8415	8765	9100
20 FR	7575	7890	8190
30 FR	6730	7010	7280
40 FR	6010	6260	6500
50 FR	5410	5635	5800
10 DW	5825	6070	6300
20 DW	5240	5460	5670
30 DW	4660	4855	5040
40 DW	4160	4335	4500
50 DW	3745	3900	4000

Printed on 04/12/2022 02:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..