

FLOTATION 648 - Tekniska specifikationer



Description

FLOTATION 648 lämpar sig särskilt väl för åker- och vägtransporter samt spridningsarbeten. Vissa storlekar är designade för skördemaskiner/balpressar. Den speciella mönsterdesignen möjliggör körning av tunga laster vid lågt lufttryck, och garanterar samtidigt låg jordpackning och bevarade grödor.

UM

US Standard

Construction

BIAS

Machinery

Lantbruk: Balpress, Höskördemaskin, Spridare

Version	STANDARD
Type	TL
Tyre Size	700/50 - 22.5
LI/SS DRIVE WHEEL	156 A8/153 B
LI/SS FREE ROLLING	168 A8/164 B

Dimensions US Standard

Usa code	94006496
Ply Rating	12
Section Width (inch)	27.6
Overall Diameter (inch)	50
Static Loaded Radius (inch)	21.7
Rolling Circumference (inch)	148.6
Rim Rec	24.00
ECE	E4-106R-002270

Load capacity (lbs)

mph / psi	22	23	26
5 FR	15540	16130	17280
10 FR	13990	14520	15550
20 FR	12430	12900	13820
25 FR	11100	11520	12350
30 FR	9990	10370	11020
5 DW	11100	11530	12350
10 DW	9990	10370	11110
20 DW	8870	9230	9880
25 DW	7930	8230	8820
30 DW	7130	7410	8050

Printed on 04/12/2022 03:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..