

FLOTATION 648 - Tekniska specifikationer



Description

FLOTATION 648 lämpar sig särskilt väl för åker- och vägtransporter samt spridningsarbeten. Vissa storlekar är designade för skördemaskiner/balpressar. Den speciella mönsterdesignen möjliggör körning av tunga laster vid lågt lufttryck, och garanterar samtidigt låg jordpackning och bevarade grödor.

UM

US Standard

Construction

 BIAS

Machinery

Lantbruk: Balpress • Höskördemaskin • Spridare

Version	STANDARD
Type	TL
Tyre Size	800/45 - 26.5
LI/SS DRIVE WHEEL	158 A8/155 B
LI/SS FREE ROLLING	170 A8/167 B

Dimensions US Standard

Usa code	94006557
Ply Rating	12
Section Width (inch)	31.5
Overall Diameter (inch)	54.8
Static Loaded Radius (inch)	24.8
Rolling Circumference (inch)	164.8
Rim Rec	AG 28.00
ECE	E11-106R-004557

Load capacity (lbs)

mph / psi	22	23	25
5 FR	17210	17870	18520
10 FR	15490	16080	16670
20 FR	13770	14300	14810
25 FR	12290	12760	13230
30 FR	11070	11490	12010
5 DW	12190	12650	13120
10 DW	10970	11390	11810
20 DW	9750	10120	10490
25 DW	8710	9040	9370
30 DW	7840	8130	8540

Printed on 11/29/2023 5:00 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..