

FLOTATION RIB 774 - Ladda ned faktablad



Description

FLOTATION RIB 774 lämpar sig för alla frirullande användningsområden och höskörningsarbeten och är utmärkt för släpvagnar. Det är designat för att erbjuda maximal hanteringskomfort som optimerar drifttiden samt hög lastkapacitet och längre livslängd för däck.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Skördemaskin • Höskördemaskin • Släpvagn

SIZE	Version	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
550/60 - 22.5	STANDARD	160 A8/156 B	12	AG 16.00		550	1240	540	3725	TL	E11-106R-005941
550/60 - 22.5	STANDARD	167 A8/163 B	16	AG 16.00		550	1240	540	3725	TL	E11-106R-005942
600/55 - 22.5	STANDARD	169 A8/166 B	16	AG 20.00		600	1230	540	3716	TL	E11-106R-005944
600/55 - 22.5	STANDARD	164 A8/160 B	12	AG 20.00		600	1230	540	3716	TL	E11-106R-005943

Printed on 4/17/2024 3:50 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..