

FLOTATION TR 678 - Tekniska specifikationer



Description

FLOTATION TR 678 är specialkonstruerat för släpvagnar och arbetsfordon i lantbruket för körning på både väg och åker. Däcket möjliggör körning av väldigt tunga laster vid lågt lufttryck, och garanterar samtidigt låg jordpackning. Det ger utmärkt dragförmåga och erbjuder enastående självrensande egenskaper.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Arbetsfordon • Släpvagn

Version	INDUSTRIAL
Type	TL
Tyre Size	600/40 - 22.5
LI/SS DRIVE WHEEL	157 A8
LI/SS FREE ROLLING	169 A8

Dimensions International Standard

Ply Rating	20
Section Width (mm)	615
Overall Diameter (mm)	1085
Static Loaded Radius (mm)	483
Rolling Circumference (mm)	3264
Rim Rec	AG 20.00

Load capacity (Kg)

	km/h / bar	4.10
	40 FR	5800
	40 DW	4125

Printed on 2/26/2024 11:05 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..