

FLOTATION TR 678 - Tekniska specifikationer



Description

FLOTATION TR 678 är specialkonstruerat för släpvagnar och arbetsfordon i lantbruket för körning på både väg och åker. Däcket möjliggör körning av väldigt tunga laster vid lågt lufttryck, och garanterar samtidigt låg jordpackning. Det ger utmärkt dragförmåga och erbjuder enastående självrensande egenskaper.

UM

US Standard

Construction

 BIAS

Machinery

Lantbruk: Arbetsfordon • Släpvagn

Version	STANDARD
Type	TL
Tyre Size	650/45 - 22.5
LI/SS	166 B

Dimensions US Standard

Usa code	94026517
Ply Rating	20
Section Width (inch)	25.6
Overall Diameter (inch)	45.3
Static Loaded Radius (inch)	19.8
Rolling Circumference (inch)	130
Rim Rec	AG 20.00
ECE	E11-106R-004400

Load capacity (lbs)

mph / psi	65
30	11680

Printed on 2/23/2024 1:20 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..