

FLOTATION TR 678 - Tekniska specifikationer



Description

FLOTATION TR 678 är specialkonstruerat för släpvagnar och arbetsfordon i lantbruket för körning på både väg och åker. Däcket möjliggör körning av väldigt tunga laster vid lågt lufttryck, och garanterar samtidigt låg jordpackning. Det ger utmärkt dragförmåga och erbjuder enastående självrensande egenskaper.

UM

US Standard

Construction

 BIAS

Machinery

Lantbruk: Arbetsfordon • Släpvagn

Version	ARAMID + STEEL BELTED
Type	TL
Tyre Size	710/40 - 22.5
LI/SS	173 A8

Dimensions US Standard

Usa code	94064755
Section Width (inch)	27.8
Overall Diameter (inch)	45.9
Rim Rec	AG 24.00
ECE	E11-106R-006011

Load capacity (lbs)

	mph / psi	87
	25	14300

Printed on 2/26/2024 10:49 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..