

FORESTECH - Tekniska specifikationer



Description

FORESTECH är ett stålbeltat radialdäck från BKT. Det passar bra för skogsavverkning med skotare. Det har utmärkt dragkraft även vid tung användning. Den kraftiga däckfoten och skulderområdet ger ett gott skydd mot punktering samt en längre livscykel. Du kan därför ta dig an de mest svåra driftförhållanden i skogen utan att behöva oroa dig.

UM

US Standard

Construction

 BIAS

Machinery

Lantbruk: Skotare

Version	STEEL BELTED
Type	TL
Tyre Size	710/40 - 22.5
LI/SS	161 A8/ 165 A2

Dimensions US Standard

Usa code	94059683
Ply Rating	20
Section Width (inch)	28
Overall Diameter (inch)	45.9
Static Loaded Radius (inch)	21.7
Rolling Circumference (inch)	142.2
Rim Rec	AG 24.00
ECE	E11-106R-005273
TRA Code	LS2

Load capacity (lbs)

mph / psi	73
25	10200
20	11025
5	11400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 01/05/2025 06:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..