

FS 216 - Tekniska specifikationer



Description

FS 216 har en robust blockdesign med optimal vinkel och större bredd för att ge bättre dragkraft för skördare och lunnare. Det har ett utomordentligt skydd mot skär- och skrapskador under de mest kritiska användningsförhållandena och ger maximalt skydd mot möjliga skador i alla lägen.

UM

US Standard

Construction

 BIAS

Machinery

Lantbruk: Lunnare

Version	STEEL BELTED
Type	TT
Tyre Size	18.4 - 30

Dimensions US Standard

Usa code	94028115
Ply Rating	10
Section Width (inch)	18.4
Overall Diameter (inch)	62.1
Static Loaded Radius (inch)	28.5
Rolling Circumference (inch)	186.5
Rim Rec	DW 16 A
ECE	E11-106R-003638
TRA Code	LS2

Load capacity (lbs)

mph / psi	30	25
5	8420	-
20	-	6010

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/3/2025 12:36 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..