

FS 216 - Tekniska specifikationer



Description

FS 216 har en robust blockdesign med optimal vinkel och större bredd för att ge bättre dragkraft för skördare och lunnare. Det har ett utomordentligt skydd mot skär- och skrapskador under de mest kritiska användningsförhållandena och ger maximalt skydd mot möjliga skador i alla lägen.

UM

US Standard

Construction

 BIAS

Machinery

Lantbruk: Lunnare

Version	STEEL BELTED
Type	TL
Tyre Size	24.5 - 32

Dimensions US Standard

Usa code	94033669
Ply Rating	16
Section Width (inch)	24.5
Overall Diameter (inch)	72.1
Static Loaded Radius (inch)	32.9
Rolling Circumference (inch)	214.8
Rim Rec	DH 21
Rim Alt	DH 21 B
ECE	E11-106R-003421
TRA Code	LS2

Load capacity (lbs)

mph / psi	35	30
5	15400	-
20	-	11000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/2/2025 1:46 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..