

## GIANT TRAX - Tekniska specifikationer



### Description

GIANT TRAX är ett däck som passar kompaktlastare som används på tuffa underlag, till exempel på anläggningar för avfallshandling och återvinning samt i gruvor. Det extra djupa slitbanemönstret med bredare och kraftigare block ger bästa möjliga dragkraft, stabilitet och skydd mot punkteringar. Den speciella gummiblandningen i slitbanan ger ett utomordentligt skydd mot skär- och skrapskador och ger däckets en utmärkt slitstyrka i alla typer av terräng.

### UM

International Standard

### Construction

❖ BIAS

### Machinery

Industri: Kompaktlastare

Version	STANDARD
Type	TL
Tyre Size	10 - 16.5

## Dimensions International Standard

Ply Rating	12
Section Width (mm)	270
Overall Diameter (mm)	775
Static Loaded Radius (mm)	362
Rolling Circumference (mm)	2317
Rim Rec	8.25
ECE	E11-106R-003579

## Load capacity (Kg)

km/h / bar	6.20
10	2375
15	1875
25	1730

Printed on 4/19/2024 8:19 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..