

GR 288 - Tekniska specifikationer



Description

GR 288 (G-2/L-2) är ett mångsidigt diagonaldäck för vägghylar och hjullastare. Det är idealiskt för användning vid anläggningsarbeten, markarbeten, vägbyggen och i andra mjuka och leriga miljöer. Det självrensande slitbanemönstret ger utmärkt dragförmåga och den skär- och rivtåliga gummiblandningen i slitbanan ger däckets en lång livslängd.

UM

US Standard

Construction

 BIAS

Machinery

Industri: Bulldozer • Hjullastare

OTR: Vägghylare

Version	STANDARD
Type	TL
Tyre Size	17.5 - 25

Dimensions US Standard

Usa code	94014439
Ply Rating	16
Overall Width (inch)	17.5
Overall Diameter (inch)	52.4
Static Loaded Radius (inch)	23.5
Rolling Circumference (inch)	155.5
Rim Rec	14.00/1.5
Rim Alt	14.00/1.3 (DC)
ECE	E11-106R-004561
TRA Code	G2/L2

Load capacity (lbs)

mph / psi	40	69
25	7400	-
5	-	16100

Printed on 4/28/2024 4:41 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..