

GRIP STAR - Tekniska specifikationer



Description

GRIP STAR är ett däck för jordbruksindustrin. Det passar bra för lastning med teleskoplastare. Det har utmärkt dragkraft och utmärkta självrensande egenskaper. Det är dessutom ett året runt-däck som passar extra bra för användning på lerig mark. GRIP STAR finns även tillgängligt i en specialversion med extra högt skydd mot skär- och skrapskador.

UM

US Standard

Construction

 BIAS

Machinery

Industri: Teleskoplastare

Version	STANDARD
Type	TL
Tyre Size	15.5/80 - 24
LI/SS DRIVE WHEEL	151 A6
LI/SS FREE ROLLING	163 A6

Dimensions US Standard

Usa code	94019762
Ply Rating	16
Section Width (inch)	15.4
Overall Diameter (inch)	50
Static Loaded Radius (inch)	22.4
Rolling Circumference (inch)	145
Rim Rec	W 12
Rim Alt	W 13 ; W 14 L

Load capacity (lbs)

mph / psi	58
20 FR LLV	10750
20 DW LLV	7610

Printed on 4/19/2024 3:20 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..