

## HARVESTER SPECIAL - Tekniska specifikationer



### Description

HARVESTER SPECIAL är särskilt konstruerat för skördemaskiner. De dubbla, vinklade däcklackarna ger utmärkt dragförmåga på åkern och bekväm körning på väg. Den speciella mönsterdesignen skapar en stor kontaktyta för överlägsen stabilitet. HARVESTER SPECIAL har ett starkt däckhölje och gummiblandningen ger extra motståndskraft mot skärande underlag och punkteringar för att garantera längre livslängd.

### UM

International Standard

### Construction

 BIAS

### Machinery

Lantbruk: Skördemaskin

Version	DUAL BEAD
Type	TL
Tyre Size	23.1 - 26
LI/SS	159 A6

## Dimensions International Standard

Ply Rating	16
Section Width (mm)	587
Overall Diameter (mm)	1585
Static Loaded Radius (mm)	720
Rolling Circumference (mm)	4806
Rim Rec	DW 20 B ; DW 20 A
TRA Code	R1

## Load capacity (Kg)

km/h / bar	2.30
30	4375

Printed on 5/23/2024 8:21 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..