

HARVESTER SPECIAL - Ladda ned faktablad



Description

HARVESTER SPECIAL är särskilt konstruerat för skördemaskiner. De dubbla, vinklade däcklackarna ger utmärkt dragförmåga på åkern och bekväm körning på väg. Den speciella mönsterdesignen skapar en stor kontaktyta för överlägsen stabilitet. HARVESTER SPECIAL har ett starkt däckhölje och gummiblandningen ger extra motståndskraft mot skärande underlag och punkteringar för att garantera längre livslängd.

UM

US Standard

Construction

 BIAS

Machinery

Lantbruk: Skördemaskin

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
23.5 - 25	DUAL BEAD	94065882	R1		20	19.50/2.5		24.2	65.6	28.1	199.1	TL	E11-106R-006954
23.1 - 26	DUAL BEAD	94062089	R1	155 A8	16	DW 20 B ; DW 20 A		23.1	62.4	28.3	189.2	TL	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/3/2025 11:13 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..