

I - 1 - Tekniska specifikationer



Description

I-1 har utvecklats för fält- och vägtransport samt jordbearbetning med arbetsfordon och släp. I-1 är ett höghastighetsdäck som optimerar körtiderna så att du kan fokusera på din kärnverksamhet. Den speciella konstruktionen ger lång livslängd även under tuffa omständigheter och om det finns stubb på fälten.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Arbetsfordon • Släpvagn

| | |
|-----------|-------------------|
| Version | STUBBLE RESISTANT |
| Type | TL |
| Tyre Size | 11L - 15 SL |
| LI/SS | 121 D |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Ply Rating | 12 |
| Section Width (mm) | 270 |
| Overall Diameter (mm) | 770 |
| Static Loaded Radius (mm) | 342 |
| Rolling Circumference (mm) | 2256 |
| Rim Rec | 8 LB |
| Rim Alt | 10 LB |
| ECE | E11-106R-004575 |
| TRA Code | I1 |

Load capacity (Kg)

| km/h / bar | 3.60 |
|------------|------|
| 65 | 1450 |

Printed on 12/4/2023 11:13 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..