

I - 1 - Tekniska specifikationer



Description

I-1 har utvecklats för fält- och vägtransport samt jordbearbetning med arbetsfordon och släp. I-1 är ett höghastighetsdäck som optimerar körtiderna så att du kan fokusera på din kärnverksamhet. Den speciella konstruktionen ger lång livslängd även under tuffa omständigheter och om det finns stubb på fälten.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Arbetsfordon • Släpvagn

Version	STANDARD
Type	TT
Tyre Size	12.5L - 15 SL

Dimensions International Standard

Ply Rating	12
Section Width (mm)	310
Overall Diameter (mm)	820
Static Loaded Radius (mm)	362
Rolling Circumference (mm)	2403
Rim Rec	10 LB
ECE	E11-106R-003371
TRA Code	I1

Load capacity (Kg)

km/h / bar	3.60
65	1750

Printed on 4/17/2024 11:49 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..