

## I - 1 - Tekniska specifikationer



### Description

I-1 har utvecklats för fält- och vägtransport samt jordbearbetning med arbetsfordon och släp. I-1 är ett höghastighetsdäck som optimerar körtiderna så att du kan fokusera på din kärnverksamhet. Den speciella konstruktionen ger lång livslängd även under tuffa omständigheter och om det finns stubb på fälten.

### UM

International Standard

### Construction

 BIAS

### Machinery

Lantbruk: Arbetsfordon • Släpvagn

Version	STANDARD
Type	TT
Tyre Size	12.5L - 16 SL

## Dimensions International Standard

Ply Rating	10
Section Width (mm)	310
Overall Diameter (mm)	845
Static Loaded Radius (mm)	374
Rolling Circumference (mm)	2476
Rim Rec	10 LB
Rim Alt	W 10 L
ECE	E11-106R-004293
TRA Code	I1

## Load capacity (Kg)

km/h / bar	3.00
65	1600

Printed on 4/17/2024 6:54 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..