

## I - 1 - Tekniska specifikationer



### Description

I-1 har utvecklats för fält- och vägtransport samt jordbearbetning med arbetsfordon och släp. I-1 är ett höghastighetsdäck som optimerar körtiderna så att du kan fokusera på din kärnverksamhet. Den speciella konstruktionen ger lång livslängd även under tuffa omständigheter och om det finns stubb på fälten.

### UM

International Standard

### Construction

 BIAS

### Machinery

Lantbruk: Arbetsfordon • Släpvagn

Version	STANDARD
Type	TL
Tyre Size	19L - 16.1 SL

## Dimensions International Standard

Ply Rating	14
Section Width (mm)	490
Overall Diameter (mm)	1100
Static Loaded Radius (mm)	474
Rolling Circumference (mm)	3223
Rim Rec	W 16 C
Rim Alt	W 16 CH
ECE	E11-106R-006676
TRA Code	I1

## Load capacity (Kg)

km/h / bar	2.80
65	3150

Printed on 4/18/2024 2:03 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..