

INDUSTRIAL RIB F3 - Tekniska specifikationer



Description

INDUSTRIAL RIB F3 är ett agroindustriidäck med mönsterribbor och har utvecklats för fält- och vägtransport samt jordbearbetning med arbetsfordon och släp. Detta däck har en enastående gummiblandning med motståndskraft mot stubb vilket gör det lämpligt för de mest kritiska driftförhållandena och säkerställer en lång livslängd för däcket.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Arbetsfordon • Släpvagn

Version	STUBBLE RESISTANT
Type	TL
Tyre Size	11L - 15 SL
LI/SS	117 A6

Dimensions International Standard

Ply Rating	12
Section Width (mm)	279
Overall Diameter (mm)	813
Rim Rec	8 LB
Rim Alt	10 LB
ECE	E11-106R-005311
TRA Code	F3

Load capacity (Kg)

km/h / bar	4.20
30	1290
40	1160

Printed on 4/25/2024 10:48 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..