

IT 400 - Tekniska specifikationer



Description

IT 400 är ett vägorienterat däck med ribbmönster, avsett för lågbyggda släp som används för transporter. Det passar för användning i höga hastigheter och ger stora bränslebesparingar.

UM

US Standard

Construction

 BIAS

Machinery

Industri: Släpvagn med låg plattform

Version	STANDARD
Type	TT
Tyre Size	7.50 - 15
LI/SS	125/121 J

Dimensions US Standard

Usa code	94008278
Ply Rating	16
Section Width (inch)	8.3
Overall Diameter (inch)	31.3
Static Loaded Radius (inch)	14
Rolling Circumference (inch)	93
Rim Rec	6.0
Rim Alt	5.50 F ; 6.50
ECE	E11-54R-0019535

Load capacity (lbs)

mph / psi	125	115
62 LS	3650	-
62 LD	-	3210

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/3/2025 6:41 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..