

JUMBO TRAX HD - Tekniska specifikationer



Description

JUMBO TRAX HD är ett blockmönsterdäck för kompaktlastare. Det har ett skydd mot skär- och skrapskador och är därför särskilt lämpligt för tung användning. Det djupa mönstret ger, tillsammans med det utmärkta sidovägsskyddet, däcket längre livslängd. JUMBO TRAX HD finns även tillgängligt i en specialversion.

UM

International Standard

Construction

 BIAS

Machinery

Industri: Kompaktlastare

Version	STANDARD
Type	TL
Tyre Size	10 - 16.5

Dimensions International Standard

Ply Rating	10
Section Width (mm)	268
Overall Diameter (mm)	795
Static Loaded Radius (mm)	363
Rolling Circumference (mm)	2345
Rim Rec	8.25

Load capacity (Kg)

km/h / bar	5.20
10	2135
15	1685
25	1560

Printed on 4/27/2024 10:47 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..