

## LG 306 - Tekniska specifikationer



### Description

LG 306 är ett däck för gräsmatta och trädgård och lämpar sig för åkgräsklippare. I vissa storlekar passar LG 306 även till små traktorer. Det speciella mönstret gör att däckets skonsamt mot marken och samtidigt enkelt att hantera. LG 306 finns även i en version "med stålbalte" för användare som behöver extra hög motståndskraft mot punkteringar.

### UM

International Standard

### Construction

 BIAS

### Machinery

Lantbruk: Åkgräsklippare • Liten traktor

Version	STANDARD
Type	TL
Tyre Size	18 X 9.50 - 8

## Dimensions International Standard

Ply Rating	4
Section Width (mm)	230
Overall Diameter (mm)	470
Static Loaded Radius (mm)	206
Rolling Circumference (mm)	1363
Rim Rec	7.00 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-003449

## Load capacity (Kg)

km/h / bar	1.40
15	425

Printed on 4/26/2024 6:44 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..