

## LG 307 - Tekniska specifikationer



### Description

LG 307 är ett däck för gräsklippningsmaskiner som används på gräsmattor och i trädgårdar. Det speciella slitbanemönstret är skonsamt mot marken för att förhindra skador på gräsytor och ger däckets goda köregenskaper.

### UM

International Standard

### Construction

 BIAS

### Machinery

Lantbruk: Åkgräsklippare

Version	STANDARD
Type	TL
Tyre Size	20 X 10.00 - 8

## Dimensions International Standard

Ply Rating	6
Section Width (mm)	255
Overall Diameter (mm)	495
Static Loaded Radius (mm)	215
Rolling Circumference (mm)	1435
Rim Rec	8.00 I - 55 ; I - 70 ; I - 90
Rim Alt	7.00 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-003462

## Load capacity (Kg)

km/h / bar	2.20
15	670

Printed on 4/25/2024 4:02 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..