

LG 408 - Tekniska specifikationer



Description

LG 408 är ett däck för gräsmatta och trädgård och lämpar sig för åkgräsklippare och små traktorer. Det speciella mönstret gör att däcket är skonsamt mot marken för att förhindra skador på gräsmattan och gör det samtidigt enklare att hantera. LG 408 finns även i en version "med stålbälte" för användare som behöver extra hög motståndskraft mot punkteringar.

UM

US Standard

Construction

 BIAS

Machinery

Lantbruk: Åkgräsklippare • Liten traktor

Version	STANDARD
Type	TL
Tyre Size	24 X 13.00 - 12

Dimensions US Standard

Usa code	94012862
Ply Rating	4
Section Width (inch)	12.8
Overall Diameter (inch)	24
Static Loaded Radius (inch)	10.6
Rolling Circumference (inch)	69.1
Rim Rec	10.5 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-005204

Load capacity (lbs)

mph / psi	20
10	1840

Printed on 4/25/2024 5:39 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..