



# LG RIB PLUS - Tekniska specifikationer



## Description

LG RIB PLUS är ett däck för gräsmatta och trädgård och lämpar sig för användning med gräsklippare, små traktorer och hövändare. Mönstret är specialdesignat för att däcket ska vara skonsamt mot marken och förhindra skador på gräsmattan och samtidigt underlätta arbetet. Tack vare den runda profilen kan LG RIB PLUS enkelt glida och kana under svängar på fältet.

## UM

US Standard

## Construction

❖ BIAS

## Machinery

Lantbruk: Åkgräsklippare • Liten traktor

Version	STANDARD
Type	TL
Tyre Size	16 X 6.50 - 8

## Dimensions US Standard

Usa code	94065530
Ply Rating	10
Section Width (inch)	6.7
Overall Diameter (inch)	16.1
Rim Rec	5.375 I - 55 ; I - 70 ; I - 90

## Load capacity (lbs)

mph / psi	72
10	1060

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/2/2025 12:27 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..