

LG RIB - Tekniska specifikationer



Description

LG RIB är ett däck för gräsmatta och trädgård och lämpar sig för åkgräsklippare och små traktorer. Mönstret gör att däckets skonsamt mot marken för att förhindra skador på gräsmattan och gör det samtidigt enklare att hantera. LG RIB finns även i en version "med stålbalte" för användare som behöver extra hög motståndskraft mot punkteringar.

UM

US Standard

Construction

❖ BIAS

Machinery

Lantbruk: Åkgräsklippare • Liten traktor

Version	ARAMID BELTED
Type	TL
Tyre Size	16 X 6.50 - 8

Dimensions US Standard

Usa code	94013036
Ply Rating	6
Section Width (inch)	6.7
Overall Diameter (inch)	16.1
Static Loaded Radius (inch)	7.2
Rolling Circumference (inch)	46.6
Rim Rec	5.375 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-003499

Load capacity (lbs)

mph / psi	42
10	785

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 3:49 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..