

LIFT STAR PLUS - Tekniska specifikationer



Description

LIFT STAR PLUS är ett diagonaldäck för teleskoplastare som används vid krävande bygg- och anläggningsarbeten samt andra tuffa arbeten. Sidoväggens låga profil ger utmärkt stabilitet vid höga lyft och det symmetriska slitbanemönstret ger högre flexibilitet vid monteringen. Den specialdesignade sidoväggen ger dessutom extra skydd mot skärskador och punkteringar.

UM

US Standard

Construction

 BIAS

Machinery

Industri: Teleskoplastare

Version	STANDARD
Type	TL
Tyre Size	400/75 - 28

Dimensions US Standard

Usa code	94046225
Ply Rating	16
Section Width (inch)	15.7
Overall Diameter (inch)	51.9
Static Loaded Radius (inch)	23.3
Rolling Circumference (inch)	155.3
Rim Rec	12.00 GR
ECE	E11-106R-005330

Load capacity (lbs)

mph / psi	51	73
30	8545	-
5	-	13890

Printed on 11/28/2023 4:41 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..