

LIFTMAX LM 63 - Tekniska specifikationer



Description

LIFTMAX LM 63 har utvecklats speciellt för industri- och logistikverksamhet. Designen med tre slitbanor ger ett lågt rullmotstånd med bra våtgrepp och ett jämnt slitage för slitbanan med bättre hantering. Det är ett radiellt däck gjort helt i stål med flera lager stålbälten som ger lägre vibrationer samt förbättrad stabilitet och komfort.

UM

US Standard

Construction

 RADIAL

Machinery

Lantbruk: Höskördemaskin

Industri: Tow Tractor • Släpvagn

Version	STANDARD
Type	TL
Tyre Size	180/70 R 8 (18X7 R 8)
LI/SS	125 A5

Dimensions US Standard

Usa code	94067008
Overall Width (inch)	6.7
Overall Diameter (inch)	18.1
Rim Rec	4.33R

Load capacity (lbs)

mph / psi	145
15	3640

Printed on 4/17/2024 4:51 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..