

## LIFTMAX LM 63 - Ladda ned faktablad



### Description

LIFTMAX LM 63 har utvecklats speciellt för industri- och logistikverksamhet. Designen med tre slitbanor ger ett lågt rullmotstånd med bra våtgrepp och ett jämnt slitage för slitbanan med bättre hantering. Det är ett radiellt däck gjort helt i stål med flera lager stålbälten som ger lägre vibrationer samt förbättrad stabilitet och komfort.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Lantbruk: Höskördemaskin

Industri: Tow Tractor • Släpvagn

SIZE	Version	LI/SS	RIM REC	RIM ALT	OW	OD	Type	ECE
<b>180/70 R 8 (18X7 R 8)</b>	STANDARD	125 A5	4.33R		170	460	TL	
<b>180/70 R 8 IMP (18X7 R 8)</b>	STANDARD	120 A8	4.33R		170	460	TL	E11-106R-006845
<b>6.00 R 9</b>	STANDARD	121 A5	4.00E		160	542	TL	
<b>6.50 R 10</b>	STANDARD	128 A5	5.00F	5.50 F	176	592	TL	
<b>7.00 R 12</b>	STANDARD	136 A5	5.00S		195	675	TL	
<b>7.00 R 15</b>	STANDARD	143 A5	5.50	5.00	198	738	TL	
<b>8.25 R 15</b>	STANDARD	153 A5	6.5	7.0	240	844	TL	

Printed on 4/17/2024 5:06 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..