

LOADER SPECIAL - Tekniska specifikationer



Description

LOADER SPECIAL (L-5) är ett diagonaldäck som ser till att dina hjullastare är i gång och arbetar så effektivt som möjligt med tunga stenarbeten. Den optimala dragkraften och det utomordentliga motståndet mot skärskador höjer produktiviteten.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Bulldozer • Hjullastare

Version	STANDARD
Type	TL
Tyre Size	20.5 - 25

Dimensions International Standard

Ply Rating	20
Overall Width (mm)	530
Overall Diameter (mm)	1570
Rim Rec	17.00/2.0
TRA Code	L5

Load capacity (Kg)

km/h / bar	4.50
10	9500

Printed on 4/17/2024 4:32 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..