

LUG STAR - Tekniska specifikationer



Description

LUG STAR är ett industridäck designat för grävarbeten inom väg och järnväg som kräver dragförmåga utöver det vanliga. Däcket har enastående självrensande egenskaper och gummiblandningen är väldigt slitstark. Det robusta däckhöljet ger utmärkt hållbarhet.

UM

International Standard

Construction

 BIAS

Machinery

Industri: Utrustning för väg och järnväg

Version	STANDARD
Type	TT
Tyre Size	10.00 - 20

Dimensions International Standard

Ply Rating	14
Overall Width (mm)	280
Overall Diameter (mm)	1080
Static Loaded Radius (mm)	506
Rolling Circumference (mm)	3343
Rim Rec	7.5
Rim Alt	7.0 ; 8.0

Load capacity (Kg)

km/h / bar	5.00
50	2470

Printed on 4/25/2024 10:41 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..