

## MAGLIFT ECO RIB - Tekniska specifikationer



### Description

MAGLIFT ECO RIB är ett massivt däck som har designats speciellt för GSE-släpvagnar (markutrustning). Den förstärkta strukturen minimerar risken för slirning, samtidigt som det specialdesignade fälgskyddet skyddar mot skador på hjulen. MAGLIFT ECO RIB har utmärkt styrkontroll, hög stabilitet, låg vibration och lastfördelning för släpvagnar. Ytterligare funktioner är lågt rullningsmotstånd och liten värmebildning för högre effektivitet.

### UM

International Standard

### Construction

◆ SOLID

### Machinery

Industri: Gaffeltruck

Version	STANDARD
---------	----------

Type	
------	--

Tyre Size	4.00 - 8
-----------	----------

## Dimensions International Standard

Section Width (mm)	104
Overall Diameter (mm)	406
Rim Rec	3.00 D - 8

## Load capacity (Kg)

km/h / bar	-
5 OTHER VEHICLES	950
10 OTHER VEHICLES	860
25 OTHER VEHICLES	730

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/7/2024 10:29 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..