

MAGLIFT ECO RIB - Tekniska specifikationer



Description

MAGLIFT ECO RIB är ett massivt däck som har designats speciellt för GSE-släpvagnar (markutrustning). Den förstärkta strukturen minimerar risken för slirning, samtidigt som det specialdesignade fälgskyddet skyddar mot skador på hjulen. MAGLIFT ECO RIB har utmärkt styrkontroll, hög stabilitet, låg vibration och lastfördelning för släpvagnar. Ytterligare funktioner är lågt rullningsmotstånd och liten värmebildning för högre effektivitet.

UM

US Standard

Construction

◆ SOLID

Machinery

Industri: Gaffeltruck

| | |
|-----------|----------|
| Version | STANDARD |
| Type | |
| Tyre Size | 4.00 - 8 |

Dimensions US Standard

| | |
|-------------------------|------------|
| Usa code | 94062157 |
| Section Width (inch) | 4.1 |
| Overall Diameter (inch) | 16 |
| Rim Rec | 3.00 D - 8 |

Load capacity (lbs)

| mph / psi | - |
|-------------------|------|
| 3 OTHER VEHICLES | 2095 |
| 5 OTHER VEHICLES | 1895 |
| 15 OTHER VEHICLES | 1610 |

Printed on 4/26/2024 5:14 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..