

## MAGLIFT ECO - Tekniska specifikationer



### Description

MAGLIFT ECO har designats speciellt för gaffeltruckar. Däcket har ett brett mönster av däckklackar för maximal stabilitet och optimerad lastfördelning. Den förstärkta strukturen minimerar risken för slirning, samtidigt som det specialdesignade följskyddet skyddar mot skador på hjulen. MAGLIFT ECO ger utmärkt dragförmåga samt lågt rullningsmotstånd och liten värmebildning för högre effektivitet.

### UM

US Standard

### Construction

◆ SOLID

### Machinery

Industri: Gaffeltruck

Version	STANDARD
---------	----------

Type	
------	--

Tyre Size	18 X 7 - 8 (180/70 - 8)
-----------	----------------------------

## Dimensions US Standard

Usa code	94060627
Section Width (inch)	5.2
Overall Diameter (inch)	17.8
Rim Rec	4.33 R - 8

## Load capacity (lbs)

mph / psi	-
15 LOAD WHEEL	4730
15 STEER WHEEL	3635

Printed on 4/26/2024 4:27 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..