

MAGLIFT ECO - Ladda ned faktablad



Description

MAGLIFT ECO har designats speciellt för gaffeltruckar. Däcket har ett brett mönster av däckklackar för maximal stabilitet och optimerad lastfördelning. Den förstärkta strukturen minimerar risken för slirning, samtidigt som det specialdesignade följskyddet skyddar mot skador på hjulen. MAGLIFT ECO ger utmärkt dragförmåga samt lågt rullningsmotstånd och liten värmebildning för högre effektivitet.

UM

International Standard

Construction

◆ SOLID

Machinery

Industri: Gaffeltruck

SIZE	Version	RIM REC	RIM ALT	SW	OD	Type	TKPH
15 X 4.5 - 8 (125 / 75 - 8)	LIP	3.00 D - 8		109	378		
15 X 4.5 - 8 (125 / 75 - 8)	STANDARD	3.00 D - 8		109	378		
16 X 6 - 8 (150 / 75 - 8)	LIP	4.33 R - 8		140	407		
16 X 6 - 8 (150 / 75 - 8)	STANDARD	4.33 R - 8		140	407		
18 X 7 - 8 (180/70 - 8)	LIP	4.33 R - 8		133	451		
18 X 7 - 8 (180/70 - 8)	STANDARD	4.33 R - 8		133	451		
4.00 - 8	LIP	3.00 D - 8		100	404		
4.00 - 8	STANDARD	3.00 D - 8		100	404		
5.00 - 8	LIP	3.00 D - 8		111	455		
5.00 - 8	STANDARD	3.00 D - 8		111	455		
21 X 8 - 9 (200 / 75 - 9)	LIP	6.00 E - 9		175	520		
21 X 8 - 9 (200 / 75 - 9)	STANDARD	6.00 E - 9		175	520		
6.00 - 9	LIP	4.00 E - 9		130	522		1
6.00 - 9	STANDARD	4.00 E - 9		130	522		1
200/50 - 10	LIP	6.50 F - 10		180	452		
200/50 - 10	STANDARD	6.50 F - 10		180	452		
23 X 9 - 10 (225 / 75 - 10)	LIP	6.50 F - 10		184	578		
23 X 9 - 10 (225 / 75 - 10)	STANDARD	6.50 F - 10		184	578		
6.50 - 10	LIP	5.00 F - 10		153	571		1
6.50 - 10	STANDARD	5.00 F - 10		153	571		1
27 X 10 - 12 (250 / 75 - 12)	LIP	8.00 G - 12		225	670		
27 X 10 - 12 (250 / 75 - 12)	STANDARD	8.00 G - 12		225	670		
7.00 - 12	LIP	5.00 S - 12		164	645		0
7.00 - 12	STANDARD	5.00 S - 12		164	645		0
250 - 15 (250 / 70 - 15)	LIP	7.0 - 15		209	714		
250 - 15 (250 / 70 - 15)	STANDARD	7.0 - 15		209	714		
300 - 15 (315/70-15)	LIP	8.0-15		242	820		
300 - 15 (315/70-15)	STANDARD	8.0-15		242	820		
8.15-15/28x9-15 (225/75-15)	LIP	7.0 - 15		204	691		
8.15-15/28x9-15 (225/75-15)	STANDARD	7.0 - 15		204	691		
8.25 - 15	LIP	6.5 - 15		210	808		
8.25 - 15	STANDARD	6.5 - 15		210	808		

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..