

MAGLIFT EXCAVATOR - Ladda ned faktablad



Description

MAGLIFT EXCAVATOR är specialutformat för hjulgravare som arbetar med grävning, lastning och vägarbeten. Däcket är tillverkat av en speciell gummiblandning som garanterar utmärkt motståndskraft mot skärande underlag och punkteringar samt längre livslängd. Utöver förstklassiga självrensande egenskaper ger det kraftiga däkmönstret hög hanteringskomfort tillsammans med utmärkt dragförmåga i sidled även under krävande arbetsförhållanden. Den förstärkta vulststrukturen säkerställer bästa möjliga grepp och eliminerar risken för slirning under arbetet, samtidigt som den speciella vulstformen underlättar monteringen på fälgen. MAGLIFT EXCAVATOR är ett punkterings- och underhållsfritt däck som förarna kan lita på.

UM

US Standard

Construction

◆ SOLID

Machinery

Industri: Grävmaskin

SIZE	Version	USACode	RIM REC	RIM ALT	OW	OD	Type
10.00 - 20	STANDARD	94071197	7.50 - 20		9.4	39.8	
10.00 - 20	STANDARD	94071203	8.00 - 20		9.7	39.8	
10.00 - 20	STANDARD	94071180	7.00 - 20		9.4	39.8	
12.00 - 20	STANDARD	94071111	8.50 - 20		10.4	43.3	
12.00 - 20	STANDARD	94071173	8.00 - 20		10	43.3	

Printed on 5/6/2024 5:14 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..