

MAGLIFT PREMIUM - Ladda ned faktablad



Description

MAGLIFT PREMIUM är ett massivt däck som är specialkonstruerat för tung användning av gaffeltruckar i hamn-, gruv- eller skrotupplagsmiljöer. Det extra djupa mönstret (25 % djupare än standardversionen) är kraftigt och robust, vilket ger enastående dragförmåga framåt och i sidled samt utmärkt styrkontroll. Den unika gummblandningen ger hög motståndskraft mot skärande underlag och punkteringar i ett däck med längre livslängd. Ytterligare egenskaper är lågt rullmotstånd och jämn körning.

UM

International Standard

Construction

◆ SOLID

Machinery

Industri: Gaffeltruck

SIZE	Version	RIM REC	RIM ALT	SW	OD	Type
6.00 - 9	LIP	4.00 E - 9		137	536	
6.00 - 9	LIP - NON MARKING	4.00 E - 9		137	536	
6.00 - 9	STANDARD	4.00 E - 9		137	536	
6.00 - 9	STANDARD - NON MARKING	4.00 E - 9		137	536	
6.50 - 10	LIP	5.00 F - 10		150	582	
6.50 - 10	STANDARD	5.00 F - 10		150	582	
7.00 - 12	LIP	5.00 S - 12		163	664	
7.00 - 12	STANDARD	5.00 S - 12		163	664	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/7/2025 12:59 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..