

MAGLIFT RIM GUARD - Ladda ned faktablad



Description

MAGLIFT (FÄLGSKYDD) är speciellt konstruerat och designat för tunga gaffeltruckar som används i industri- och logistikanläggningar. Dess aggressiva och robusta slitbanemönster ger överlägset grepp framåt och i sidled samt utmärkt styrkontroll. Dessutom ger den breda mittribban ett lågt rullningsmotstånd. Den gedigna konstruktionen med MAGLIFT (FÄLGSKYDD) har hög lastkapacitet och enastående komfort, samtidigt som dess specialdesignade fälgskydd säkerställer skydd mot hjulskador. Dessutom uppvisar detta däck utmärkt motståndskraft mot skär- och skrapskador vilket ger längre livslängd. MAGLIFT (FÄLGSKYDD) förstärkt struktur eliminerar glidrisk medan den speciella däckvulsten förenklar monteringen på fälgen.

UM

US Standard

Construction

◆ SOLID

Machinery

Industri: Gaffeltruck

SIZE	Version	USACode	RIM REC	RIM ALT	SW	OD	Type
6.50 - 10	STANDARD	94066285	5.00 F - 10		6.1	22.6	
6.50 - 10	STANDARD	94066308	5.50 F - 10		6.1	22.6	
7.00 - 12	STANDARD	94066292	5.00 S - 12		6.6	25.9	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/3/2025 8:28 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..